



DB100 / DB125

## DOLPHIN ELECTRONIC INFRARED TAP

- › WRAS Approved product
- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished chrome plated brass finish available from stock – Powder coated finishes also available on special order
- › Water Supply: 3/8 inch single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25LPM and 1.75LPM flow rates on special request
- › Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- › Fully BREEAM compliant - contributes to up to five BREEAM WAT1 credits
- › Power cable length – 5 meters
- › Interchangeable STD M22/24 Neoperl Aerator insert
- › Tap settings can be adjusted manually or by using remote control (DB51)
- › To combat Legionella, hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51).
- › 2 year manufacturer's warranty
- › Max water temperature 70°C
- › Very low energy usage
- › We recommend our DB61 TMV3 be used in conjunction with this Dolphin Blue tap
- › Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits
- › Power connections: soap dispenser: male / power source: female (DB69F)

<b>HEIGHT</b>	<b>172MM</b>
<b>DIAMETER</b>	<b>50MM</b>
<b>PROJECTION</b>	<b>91MM</b>

### PRODUCT CODES

- DB100C-STL** - Polished chrome battery powered
- DB125C-STL** - Polished chrome transformer powered

