



**DB5510.E**

## DOLPHIN BLUE 126MM ELECTRONIC CISTERN - NO FRAME

- › Flush cistern to be installed inside the wall and used in combination with floor standing WC pan
- › EN14055 Class two compliant
- › WRAS approved inlet valve
- › Incorporates AUKI Backflow arrangement
- › Compliant with DEFRA Interim agreement when used with our DC2006 toilet pan
- › Dual flush in-wall cistern compatible with dual flush actuators 6/3 litres (adjustable to 4.5/3 or 4/2.5)
- › 126mm thickness
- › Electronic actuation
- › Fitted with delayed refilling Inlet Valve, (saves up to 9 litres of water per day)
- › Inlet valve compliant with BS1212-4:2016
- › Working pressure from 0.1 to 16 bar
- › Resistance to atmospheric humidity (Hr <90%).
- › Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- › EN 14055 marking CL2
- › Supplied with anti-condensation lining
- › Net for easier mortar adhesion
- › The Dolphin Delayed Action Inlet Valve only opens and starts to refill the cistern once the flush is complete and the flush valve is closed, saving up to 0.5 litres of water per flush

<b>HEIGHT</b>	<b>530-745MM</b>
<b>WIDTH</b>	<b>488MM</b>
<b>RECESS DEPTH</b>	<b>126MM</b>

### PRODUCT CODES

- DB5510.E** - Electronic Cistern
- DB5510.P** - Pneumatic Cistern
- DB5511.E** - Electronic Cistern with Frame
- DB5511.P** - Pneumatic Cistern with Frame