



DB5500.E.AU

DOLPHIN SLIMLINE ELECTRONIC CISTERN - FRAMELESS

- › Concealed WC cistern for floor mounted/free standing WC pans
- › In painted profile corrosion resistant
- › Minimum thickness of 90mm
- › Depth adjustable outlet bend
- › Dual flush in-wall cistern compatible with dual flush actuators 4.5/3 litres
- › 80mm thickness (90mm when allowing for Ø90mm outlet bend)
- › Electronic actuation
- › Equipped with delayed refilling Inlet Valve, (can save 9 litres of water per day)
- › Working pressure from 0.1 to 16 bar
- › Resistance to atmospheric humidity (Hr <90%).
- › Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- › Supplied with anti-condensation lining
- › Pre-assembled structure for installation in front of masonry wall and finish in light wall, plasterboard wall and technical support rail for light wall
- › The Dolphin Delayed Action Inlet Valve only opens and starts to refill the cistern once the flush is complete and the flush valve is closed, saving up to 0.5 litres of water per flush
- › Compliant with WaterMark and WELS
- › Compatible with DB5590.E (Anti-vandal), DB5570.E and DB5580.E flush plates

HEIGHT	855-1015MM
WIDTH	474MM
RECESS DEPTH	90-180MM