



DB5501.P.AU

DOLPHIN SLIMLINE PNEUMATIC CISTERN - I 150MM FRAME

- > Concealed WC cistern and frame
- > In painted profile corrosion resistant
- > Minimum thickness of 80mm (90mm when allowing for Ø90mm outlet bend) and adjustable up to 145mm
- > Height regulation of the adjustable floor brackets (0-150 mm);
- > Depth adjustable outlet bend
- > Tested for 400kg load
- > Dual flush in-wall cistern compatible with dual flush actuators 4.5/3 litres
- > 90mm thickness (90mm when allowing for Ø90mm outlet bend)
- > Pneumatic actuation
- > Equipped with delayed refilling Inlet Valve, (can save 9 litres of water per day)
- > Working pressure from 0.1 to 16 bar
- > Resistance to atmospheric humidity (Hr <90%).
- > Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- > Supplied with anti-condensation lining
- > Pre-assembled structure for installation in front of masonry wall and finish in light wall, plasterboard wall and technical support rail for light wall
- > The Dolphin Delayed Action Inlet Valve only opens and starts to refill the cistern once the flush is complete and the flush valve is closed, saving up to 0.5 litres of water per flush
- > Compatible with DB5590.E (Anti-vandal), DB5570.E and DB5580.E flush plates
- > Compliant with WaterMark and WELS

HEIGHT	1150-1350MM
WIDTH	500MM
RECESS DEPTH	90-145MM